



LED DISPLAYS:ELF-4402A/B SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25℃)

Part No.	Emittd Color	PeakWave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
										Min	Max	Min	Max
ELF-4402AS	Red	620-630	White	Black	Cathode	10	35	20	60	1.8	2.0	82	92
ELF-4402AO	Orange	600-610	White	Black	Cathode	10	35	20	60	1.8	2.0	85	95
ELF-4402AY	Yellow	585-595	White	Black	Cathode	10	35	20	60	1.8	2.0	88	98
ELF-4402AG	Olivine	565-575	White	Black	Cathode	10	35	20	60	1.8	2.0	10	20
ELF-4402AGG	Emerald	515-525	White	Black	Cathode	10	55	20	60	2.6	2.8	215	225
ELF-4402AB	Blue	460-470	White	Black	Cathode	10	55	20	60	2.6	2.8	15	25
ELF-4402AW	White	-	-	Black	Cathode	-	55	20	60	2.6	2.8	-	-
ELF-4402BS	Red	620-630	White	Black	Anode	10	35	20	60	1.8	2.0	82	92
ELF-4402BO	Orange	600-610	White	Black	Anode	10	35	20	60	1.8	2.0	85	95
ELF-4402BY	Yellow	585-595	White	Black	Anode	10	35	20	60	1.8	2.0	88	98
ELF-4402BG	Olivine	565-575	White	Black	Anode	10	35	20	60	1.8	2.0	10	20
ELF-4402BGG	Emerald	515-525	White	Black	Anode	10	55	20	60	2.6	2.8	215	225
ELF-4402BB	Blue	460-470	White	Black	Anode	10	55	20	60	2.6	2.8	15	25
ELF-4402BW	White	-	-	Black	Anode	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUN RATINGS (Ta=25℃)

ReverseVoltage	ReverseCurrent (V _R =5V)	OperatingTemperature Range	StorageTemperature Range	Lead Soldering Temperature
5V	20 μ A	-35℃~+80℃	-45℃~+80℃	260℃ For 3 Seconds

PACKAGE DIMENSION (Tolerance : ±0.2mm)

