



LED DISPLAYS:ELN-3661A/B SERIES

ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25℃)

Part No.	Emittd Color	PeakWave Length	Epoxy Color	Surface Color	Common Electrode	$\Delta\lambda$ (nm)	Pd (mW)	If (mA)	Peak (mA)	Vf(V)		IV(mcd)	
										Min	Max	Min	Max
ELN-3661AS	Red	620-630	White	Black	Cathode	10	35	20	60	1.8	2.0	82	92
ELN-3661AO	Orange	600-610	White	Black	Cathode	10	35	20	60	1.8	2.0	85	95
ELN-3661AY	Yellow	585-595	White	Black	Cathode	10	35	20	60	1.8	2.0	88	98
ELN-3661AG	Olivine	565-575	White	Black	Cathode	10	35	20	60	1.8	2.0	10	20
ELN-3661AGG	Emerald	515-525	White	Black	Cathode	10	55	20	60	2.6	2.8	215	225
ELN-3661AB	Blue	460-470	White	Black	Cathode	10	55	20	60	2.6	2.8	15	25
ELN-3661AW	White	-	-	Black	Cathode	-	55	20	60	2.6	2.8	-	-
ELN-3661BS	Red	620-630	White	Black	Anode	10	35	20	60	1.8	2.0	82	92
ELN-3661BO	Orange	600-610	White	Black	Anode	10	35	20	60	1.8	2.0	85	95
ELN-3661BY	Yellow	585-595	White	Black	Anode	10	35	20	60	1.8	2.0	88	98
ELN-3661BG	Olivine	565-575	White	Black	Anode	10	35	20	60	1.8	2.0	10	20
ELN-3661BGG	Emerald	515-525	White	Black	Anode	10	55	20	60	2.6	2.8	215	225
ELN-3661BB	Blue	460-470	White	Black	Anode	10	55	20	60	2.6	2.8	15	25
ELN-3661BW	White	-	-	Black	Anode	-	55	20	60	2.6	2.8	-	-

ABSOLUTE MAXIMUM RATINGS (Ta=25℃)

ReverseVoltage	ReverseCurrent (VR=5V)	OperatingTemperature Range	StorageTemperature Range	Lead Soldering Temperature
5V	20 μ A	-20℃~+80℃	-30℃~+80℃	255℃ For 3 seconds

PACKAGE DIMENSION (Unit: millimeters, Tolerance : ± 0.25 mm)

